

imagePRESS C910/C810/C710 COLOR PRODUCTION DIGITAL PRESS





imagePRESS C910 shown with optional accessories.

PRODUCT SPECIFICATIONS

MARKING ENGINE

Technology: Electrophotography **Print Resolution:** 2400 x 2400 dpi

Print Speed

	C910	C810	C710/C710CA
8.5" x 11":	Up to 90 ppm	Up to 80 ipm	Up to 70 ipm
11" × 17":	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm
12" x 18":	Up to 42 ipm	Up to 40 ipm	Up to 35 ipm
13" x 19":	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm
13" x 30":	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm

Paper Size

Standard: 3.94" x 5.83" to 13" x 19.2" Optional: 5.5" x 5.83" to 13" x 51.2"

Paper Capacity¹

Standard: Up to 1,650 Sheets Maximum: Up to 7,650 Sheets

Paper Weight

Standard: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Optional: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Envelopes:² 3.94" x 5.83" to 13" x 19.2"

Long Sheets³

Duplex: Up to 13" x 30" Simplex: Up to 13" x 51.2"

Automatic Duplexing

Paper Size:³ Up to 13" x 30"

Paper Weight:⁴ Up to 130 lb. Cover (350 gsm)⁵ Power Source: Single-Phase 208 V, 50/60 Hz, 20 A

Weight: 697 lb.

Dimensions (W x D x H): $60.2" \times 38.7" \times 67.4"$

INPUT ACCESSORIES

Multi-Drawer Paper Deck-C1

 Paper Capacity:¹
 Up to 6,000 Sheets

 Paper Size:
 5.5" x 7.2" to 13" x 19.2"

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Power Source: 120-127 V, 60 Hz, 3.1 A

Weight: 342 lb.

Dimensions (W x D x H): $37.4" \times 31.4" \times 41"$

POD Deck Lite-C1

Paper Capacity: Up to 3,500 Sheets
Paper Size: 5.5" x 5.83" to 13" x 19.2"

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Envelopes:² 5.5" x 5.83" to 13" x 19.2" Power Source: 120-127 V, 60 Hz, 2.2 A

Weight: 168 lb.

Dimensions (W x D x H): 28.3" $\times 27.0$ " $\times 22.6$ "

POD Deck Lite XL-A1

Paper Capacity: Up to 3,500 Sheets (Up to 13" x 19.2")

Up to 1,000 Sheets (Up to 13" x 30")

Paper Size: 5.5" x 5.83" to 13" x 30"

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Envelopes:² 5.5" x 5.83" to 13" x 30" Power Source: 100-240 V, 50/60 Hz

Weight: 250 lb.

Dimensions (W x D x H): $43.5" \times 27" \times 22.6"$

imagePRESS C910 PRODUCT SPECIFICATIONS (continued)

Stack Bypass-C1

 Paper Capacity:1
 Up to 250 Sheets

 Paper Size:
 4" x 5.83" to 13" x 19.2"

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Envelopes:² 4" x 5.83" to 13" x 19.2"

Weight: 3 lb.

Dimensions (W x D x H): $19.3" \times 15.1" \times 2.9"$

Long Sheet Tray-B1

Paper Capacity: Up to 1 Sheet

Paper Size: 4" x 5.83" to 13" x 51.2"

Paper Weight: 17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm)

Envelopes: 4" x 5.83" to 13" x 19.2"

Weight: 2 lb.

Dimensions (W x D x H): 85.6" x 56.1" x 56.1"

Duplex Color Image Reader-M1

Image Sensor: CCD Scan Speed (Letter, 300 dpi)

BW (duplex): Up to 230 opm
Color (duplex): Up to 150 opm
Document Size: Statement to 11" x 17"

Resolution: Up to 600 x 600 dpi, 256 Gradations

Tray Capacity: Up 300 Sheets

Weight: 84 lb.

Dimensions (W x D x H): $25" \times 23.8" \times 10"$

FINISHING ACCESSORIES

Copy Tray-R2

Paper Capacity: Up to 250 Sheets

Paper Size: 14 lb. Bond to 130 lb. Cover (52 to 350 gsm)

Paper Weight: 4" x 5.83" to 13" x 19.2"

Weight: 2.6 lb.

Dimensions (W x D x H): $16.6" \times 15" \times 6.8"$

Document Insertion Unit-N1

Tray Capacity¹

Up to 200 Sheets
Lower Tray: Up to 200 Sheets

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 300 gsm)

Paper Size: 7.2" x 7.2" to 13" x 19.2" **Power Supply:** 100-240 V, 50/60 Hz, 1.0 A

Weight: 135 lb.

Dimensions (W x D x H): $29.4'' \times 31.3'' \times 55.4''$

Multi Function Professional Puncher-B1

Paper Weight

Punching: 20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)

Creasing: 110 lb. Text to 110 lb. Cover (162 gsm to 300 gsm)

Paper Size: 12" x 18", 11" x 17", LTR, LGL, LTR-R, STMT

Punching: Letter-R, Letter, Legal, 11" x 17", 12" x 18"
Creasing: Letter-R, 11" x 17, 12" x 18", 13" x 19"

Die Set Patterns: Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole,

Color Coil 44-Hole, Crease

Power Supply: 100-127 V, 60 Hz, 15 A

Weight: 225 lb.

Dimensions (W \times D \times H): 17.5" \times 31.3" \times 41"

GBC eWire Pro6

Bound Book Size: 15 to 80 Sheets

Paper Size: Letter, 5.5" x 8.5", Tab Stock

Paper Weight: 20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)

Wire Choices: 1/4", 5/16", 3/8", 7/16", 1/2"

Stack Capacity: Up to 35 Books

Infeed: Multi Function Professional Puncher-B1

Power Supply: 115 V, 60 Hz, 2.8A

Weight: 500 lb.

Dimensions (W x D x H): $35.8'' \times 31.3'' \times 42.6''$

Perfect Binder-E16

Finished Book Size: 5.4" x 7.99" to 8.5" x 11.69"

Book Thickness: 10 to 200 Sheets (Up to 0.98")

Body Paper Weight: 14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)

Cover Paper Weight: 24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)

Trimming Method: 3-Side Cut/1-Side Cut/No Cut

Trim Range

Top/Bottom: 0.26" to 1.56" Side: 0.26" to 1.95"

Power Source: 208 V, 60 Hz, 2.6 A

Weight: 679 lb.

Dimensions (W x D x H): 36.3" x 31.1" x 51.3"

High-Capacity Stacker-H16

Stack Capacity: Up to 6,000 Sheets

Top Tray Capacity: Up to 200 Sheets

Paper Size: 7.2" x 7.2" to 13" x 19.2"

Paper Weight: 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)

Power Source: 120 V, 60 Hz, 10 A

Weight: 265 lb.

Dimensions (W x D x H): 35.4" x 29.3" x 44.9"

Plockmatic Multi Purpose Stacker^{6,7}

Stack Height

Sheets < 25.6": Up to 11.8" Sheets > 25.6": Up to 5.3"

Paper Size: 8.3" x 11" to 13" x 30"

Paper Weight: 100 lb. Text to 130 lb. Cover (148 gsm to 350 gsm)

Power Source: 100-240 V, 50-60 Hz, 2 A

Weight: 168 lb.

Dimensions (W x D x H): $41.8" \times 35.4" \times 26.8"$

MAX Ring Binder MB-1000C^{6,8}

Binding Capacity: 2 to 100 Sheets

Sheet Size: Letter, Letter Tab

Paper Weight: 17 lb. Bond to 80 lb. Cover (64 to 216 gsm)

Stacking Capacity: Up to 25 Books

Ring Elements: Small (Up to 50 Sheets), Large (Up to 100 Sheets)

Power Source: 120-127 V, 60 Hz, 2.8 A

Weight: 331 lb.

Dimensions (W x D x H): 55.5" x 26.8" x 41.8"

imagePRESS C910 PRODUCT SPECIFICATIONS (Continued)

Paper Folding Unit-J1

Double Parallel Fold: Legal, Letter-R
C/Accordion Fold: Letter-R

Z-Fold: Letter-R, 11" x 17"

Paper Weights: 14 lb. Bond to 28 lb. Bond (50 gsm to 105 gsm)

Power Source: From Finisher

Weight: 157 lb. (71 kg)

Dimensions (W x D x H): 13.3" x 31.3" x 46.9"

Staple Finisher-AC1/Booklet Finisher-AC19

Tray Capacity¹

Top Tray: Up to 250 Sheets
Middle Tray: Up to 250 Sheets
Lower Tray: Up to 3,000 Sheets
Saddle-Stitch Tray: Up to 30 Booklets

Paper Weight

Stacking: 14 lb. Bond to 130 lb. Cover (52 to 350 gsm)

Corner Stapling: 14 lb. Bond to 140 lb. Index (52 to 256 gsm)

Booklet Making: 14 lb. Bond to 140 lb. Index (52 to 256 gsm)

Staple Positions: Corner, Double Side, Eco

Paper Size

Stapling: Executive, Letter-R, Letter, Legal, 11" x 17"

Saddle Finisher: 5.5" x 7.2" to 11.8" x 17"

Stapling Capacity¹

Corner/Double Side: Up to 65 Sheets
Eco Stitch: Up to 5 Sheets
Saddle Stitch: Up to 20 Sheets

V-Folding: Up to 3 Sheets without Stitch

Power Source: From the Main Unit

Weight

Staple Finisher: 80 lb. Booklet Finisher: 131 lb.

Dimensions (W x D x H): 25.5" x 25.9" x 44.1"

2/3 Hole Puncher Unit-A110

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

Paper Sizes

2-Hole: Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")

3-Hole: 11" x 17", Letter, Executive-R, Custom Size

(9.5" x 7.2" to 11.8" x 17")

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

Power Supply: From the Finisher

Staple Finisher-W1/Booklet Finisher-W1

Tray Capacity¹

Top Tray: Up to 1,000 Sheets Lower Tray: Up to 4,000 Sheets

Saddle-Stitch Tray: Up to 30 Booklets or Limitless

Paper Weight

Stacking: 14 lb. Bond to 130 lb. Cover (52 to 350 gsm)

Corner Stapling: 14 lb. Bond to 110 lb. Cover (52 to 300 gsm)

Booklet Making: 14 lb. Bond to 110 lb. Cover (52 to 300 gsm)

Staple Positions: Corner, Double Side

Paper Size

Stapling: 8.3" x 11" to 11.7" x 17" Saddle Finisher: 8.3" x 11" to 13" x 19.2"

Stapling Capacity¹

Corner/Double Side: Up to 100 Sheets
Saddle Stitch: Up to 25 Sheets

V-Folding: Up to 5 Sheets without stitch Power Source: 120-240 V, 60 Hz, 8 A

Weight

Staple Finisher: 287 lb. Booklet Finisher: 397 lb.

Dimensions (W x D x H): 31.5" x 31.3" x 48.8"

Puncher Unit-BS1^{II}

Paper Weight: Same as Main Engine

Paper Sizes

2-Hole: Legal, Letter-R, Custom Size

 $(7.\overline{2}$ " x 7.2" to 11.8" x 17")

3-Hole: 11" x 17", Letter, Executive-R, Custom Size

(9.5" x 7.2" to 11.8" x 17")

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

Punch Waste Capacity: Up to 6,000 Sheets **Power Supply:** From the Finisher

DFD Adapter and Finisher Bridge-A16

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

Supported Finishing: SDD BLM300C Professional Booklet Maker

Plockmatic BLM50/35 Professional Booklet Maker,

MAX Ring Binder MB-1000C

Requirements: Staple/Booklet Finisher-W1

Weight: 66 lb.

Dimensions (W x D x H): $23.5" \times 29.3" \times 5.9"$

Booklet Trimmer-F16,11

Margin Trimming: Front-edge Trim Trim Amount: 0.08" to 1.1"

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

Power Supply: From the Finisher

Weight: 392 lb.

Dimensions (W x D x H): 82.5" x 30.8" x 41"

Two-Knife Booklet Trimmer-A16,12

Margin Trimming: Top and Bottom Trim Amount: 0.08" to 0.59"

Paper Weight: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

 Power Supply:
 120 V/15 A

 Weight:
 320 lb.

Dimensions (W x D x H): 21.1" x 30.4" x 41"

SDD Square Fold Booklet Maker^{6,13}

Booklet Capacity¹: Up to 25 Sheets

Booklet Input Size: $4.71'' \times 8.27''$ to $9.6'' \times 12.6''$ **Booklet Output Size:** $4.71'' \times 7.87''$ to $9.6'' \times 12.6''$ **Paper Weight:** 16 lb. Bond to 110 lb. Cover

Trim Amount: 0.08" to 1.38" **Power Supply:** 120 V, 60 Hz, 15 A

Weight: 154 lb.

Dimensions (W x D x H): 44.9" x 23.6" x 44.9"

SDD Square Fold Booklet Maker with Two Knife Trim^{6,13}

Booklet Capacity¹: Up to 25 Sheets

Booklet Input Size: $4.88" \times 5.51"$ to $9.6" \times 12.6"$ Booklet Output Size: $4.88" \times 5.51"$ to $9.6" \times 12.6"$ Paper Weight:16 lb. Bond to 110 lb. Cover

Trim Amount: 0.08" to 1.38" **Power Supply:** 120 V, 60 Hz, 15 A

Weight: 573 lb.

Dimensions (W x D x H): $62.7" \times 27.6" \times 51.2"$

imagePRESS C910 PRODUCT SPECIFICATIONS (Continued)

SDD BLM300C Professional Booklet Maker^{6,8}

Up to 30 Sheets Booklet Size1: 5.5" x 9.9" to 12.6" x 18.5" Paper Size:

Paper Weight

16 lb. Bond to 64 lb. Cover (60 to 240 gsm) Body: Cover-20 lb. Bond to 110 lb. Cover (80 to 300 gsm)

Trim Amount14

0.08" to 0.63" Face. 0.08" to 1.38" Top/Bottom: Paper Rotating:15 8" x 8" to 9.1" x 12.6"

Weight:

Dimensions (W x D x H): 143.6" × 27.5" × 45.3"

Plockmatic BLM50/35 Professional Booklet Maker^{6,8}

Up to 50 Sheets Booklet Size1: 8.1" x 10.8" to 12.6" x 18" Paper Size:

Paper Weight

16 lb. Bond to 110 lb. Cover (60 to 300 gsm) Uncoated: 28 lb. Bond to 110 lb. Cover (105 to 300 gsm) Coated:

Trim Amount16

0.04" to 1" Face: 0.196" to 1.18" Top/Bottom:

8.1" x 10.9" to 9.1" x 12.7" Paper Rotating:17

1.235.7 lb. Weight:

Dimensions (W x D x H): 131.1" x 33.8" x 42.5"

PRINT SERVERS

imagePRESS Printer Kit-F1

PDL: PS, PCL, UFR

8 GB Memory: Hard Drive: 1.5 TB

PRISMAsync Print Server¹⁸

Version 7 System Software:

CPU: Intel Core i7 4770S @ 3.1 GHz

16 GR Memory: 1.5 TB Hard Drive: OS: Windows 10

Standard: Scheduler, DocBox, G7 Calibration, Page

Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple

Queues, Remote Control

Optional: E-Shredding

PRISMAsync Print Server LP19

System Software: Version 7

CPU: Intel Core i7 4770S @ 3.1 GHz

Memory: 16 GB Hard Drive: 1.5 TB 0S: Windows 10

Standard: Multiple Queues, Scheduler, Remote Manager, Color

Presets, Pixel Precise Preview, Spot Color Editing, Calibration, Realistic Preview, Digital Moire

Advanced Color Management, Power Up Package, Optional:

E-Shredding

imagePRESS Server H350

Fiery System: FS350 Pro

CPU: Intel Core i5-6500 3.2GHz up to 3.6GHz W/ Turbo

Memory: 8 GB Hard Drive: 2 TB

OS: Windows 10

Standard: Fiery Hot Folders, Virtual Printers, Unity Display,

Fiery JDF, Fiery Command Workstation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan,

Media Librarian

Optional: Graphic Arts Package, Impose, Compose, Job Master,

Fiery NX Station, JobFlow

imagePRESS Server G250

Fiery System: FS350

CPU: Intel Pentium G4400, 3.3 GHz

4 GB Memory: 500 GB Hard Drive: 0S:

Standard: Fiery Command Workstation 5, Paper Catalog, Fiery

Spot On, Fiery Remote Scan, Hot Folders License

Productivity Package, Impose, Compose, JDF Optional:

¹Based on 20 lb. Bond.

² Envelope Attachment Kit required

3 POD Deck Lite-XL or Long Sheet

Tray-B1 required.

⁴ Optional feeding accessories required.

Stocks longer than 19.2" support up to

110 lb. Cover (300 gsm).

6 Not available for the imagePRESS C710/

7 High Capacity Stacker-H1 required.

⁸ High Capacity Stacker-H1 or DFD Adapter and Finisher Bridge-A1 required.

Only available for the imagePRESS

C710 and C710CA.

OStaple Finisher-AC1 or Booklet Finisher-AC1 required.

11 Staple/Booklet Finisher-W1 required.

¹² Booklet Trimmer-F1 required.

13 Booklet Finisher-W1 and Booklet Trimmer-F1 required

14 SDD Front Trimmer required

15 SDD Rotator required.

16 FTR50 Trimmer Module required

¹⁷ RCT50 Rotate Crease Trim Module required.

¹⁸ Not available for the imagePRESS C710CA.

¹⁹ Not available for the imagePRESS C910

or C710CA.













The imagePRESS C910 Series contains multiple components, some of which are manufactured by third parties. Accordingly, Canon makes no representations or warranties with respect to such third-party products. For additional information on any Cannon or third-party accessories, contact your Authorized Canon representative. As an ENERGY STAR? Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imagePRESS, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All screen and printer output images are simulated. Not responsible for typographical errors. Specifications and availability subject to change without notice. ©2019 Canon U.S.A., Inc. All rights reserved.









