

FUJITSU Document Scanner

SP-1425



Versatile dedicated scanning for small offices

25
Pages per
minute

Duplex
Scans both
sides

**TWAIN
& ISIS®**
Supported

Sizes up to
Legal
8.5" x 14"

24-bit Color

600
Optical DPI

SP-1425

Versatile
small office scanner



Safe and reliable scanning

- Capably scans at up to 50 images per minute
- Automatic Document Feeder (ADF) and flatbed scanning options
- Scans long documents up to 120"
- Ultrasonic multi-feed detection sensor to stop misfed documents, reducing damage

Efficiently manage your documents

- ABBYY FineReader Sprint offers powerful OCR recognition in over 190 languages and conversion to Searchable PDF and Microsoft Office formats
- Presto! PageManager converts to Searchable PDF and offers great organization features and integration with various applications

Clean image processing with PaperStream IP for SP Series

PaperStream IP (PSIP) for SP Series is a TWAIN/ISIS®-compliant driver that optimizes scanned images without changing driver settings in advance. PSIP features powerful adjustments like:

- Auto Color Detection to automatically identify the best color mode for the document
- Multi-Image Output to release images in more than one output format
- Blank Page Detection to automatically remove blank pages

PaperStream Capture Lite specializes in routine scanning

The easy-to-understand interface ensures simple operation from start to finish. Routine operations like batch scanning are made quick and easy, so the SP-1425 will fit into your workflow without a lot of software to learn and drivers to configure.

Centralized fleet management

Includes Scanner Central Admin to remotely manage your entire fi Series and SP Series fleet. Effectively allocate your resources based on scan volume, consumables wear, and more.


| Consumables | | |
|------------------|--------------|--|
| Pad Unit | PA03753-0001 | Replace every 30,000 sheets or 1 year |
| Pick Roller Unit | PA03753-0002 | Replace every 200,000 sheets or 1 year |

To buy Genuine Fujitsu Parts and Consumables, visit FujitsuScannerStore.com or call 800.301.9475

Make it even better with PaperStream Capture Pro

Optional PaperStream Capture Pro software offers superior front-end capture, image processing, and options for enhanced data extraction and indexing for release.

Try it for free! Ask your reseller for a demo, visit paperstream.com, or call us at 888.425.8228.



Fujitsu Computer Products of America, Inc.
1250 East Arques Avenue, Sunnyvale, CA 94085
888.425.8228 Sales · 800.626.4686 Technical Support
us.fujitsu.com/fcpa · info@fcpa.fujitsu.com

©2019 Fujitsu Computer Products of America, Inc. All rights reserved. ABBYY™ FineReader™ Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. NewSoft, Presto! and PageManager are either registered trademarks or trademarks of NewSoft Technology Corp. ENERGY STAR® is a registered trademark of the United States. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies. Specifications subject to change without notice. Printed in USA on paper from responsible sources. Please recycle. 190329RO

Technical Specifications

| | | | |
|--|--|--|------------------|
| Document feeding methods | Automatic Document Feeder (ADF) Flatbed | | |
| Scanning modes | Simplex/Duplex in Color, Grayscale, or Monochrome | | |
| Image sensor type | Single-line CMOS-CIS x 2 (Front/Flatbed x1, Back x1) | | |
| Light source | 3 Color LED x 2 (Front/Flatbed x1, Back x1) | | |
| Multi-feed protection | Ultrasonic multi-feed detection sensor | | |
| Document size | ADF Minimum | 4.5" x 5.5" (114 mm x 140 mm) | |
| | ADF Maximum | Legal Portrait (8.5" x 14" or 216 mm x 356 mm) | |
| | Long page scanning ¹ | 8.5" x 120" (216 x 3,048 mm) | |
| | Flatbed maximum | 8.5" x 11.7" (216 x 297 mm) | |
| Paper weight | Paper | 14 - 34lb. (52 to 127 g/m ²) | |
| | Plastic card | Flatbed only | |
| Scanning speed ² | 200 or 300 dpi, Letter, Color ³ , Grayscale ³ and Monochrome ⁴ | ADF, Simplex | 25 pages/minute |
| | | ADF, Duplex | 50 images/minute |
| | Flatbed | 4 seconds (200 dpi) | |
| ADF capacity ⁵ | 50 Sheets (A4/Letter: 20 lb. or 80 g/m ²) | | |
| Background colors | ADF: White / Flatbed: Black | | |
| Output resolution ⁶ | Color (24-bit), Grayscale (8-bit), Monochrome (1-bit) | 50 to 600 dpi, 600 dpi optical, 1200 dpi software ⁷ | |
| Interface | USB 2.0 / USB 1.1 | | |
| Power requirements | 100 to 240 VAC, 50/60 Hz | | |
| Power consumption | Operating: 16 W or less | | |
| | Sleep mode: 2.9 W or less Auto-standby (Off) mode: 0.5 W or less | | |
| Operating environment | Temperature | 41° to 95°F (5° to 35°C) | |
| | Relative humidity | 20% to 80% (non-condensing) | |
| Dimensions (WxDxH) ⁸ | 17.9" x 13" x 5.1" (454 mm x 331 mm x 129 mm) | | |
| Weight | 9.5 lb (4.3 kg) | | |
| Included in the box | Pad unit, AC cable & adapter, USB cable, Setup DVD-ROM | | |
| Bundled software (DVD format) | PaperStream IP (TWAIN/ISIS) Driver, WIA Driver ⁹ , PaperStream Capture, ScanSnap Manager for fi Series ¹⁰ , ABBYY FineReader for ScanSnap ¹⁰ , Scanner Central Admin, Software Operation Panel, Error Recovery Guide | | |
| Environmental designations ¹¹ | ENERGY STAR®, RoHS | | |
| Supported operating systems | Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2019 (64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit), Linux (Ubuntu) ⁹ | | |
| Image processing functions | Multi-image output, Auto color detection, Auto page size detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-screen, Emphasis, Dropout color, sRGB output, Split image, De-skew, Edge filler, Vertical streak reduction, Digital endorser, Background pattern removal | | |

¹ When resolution is set to 200 DPI or less ² Actual scanning speeds are affected by data transmission and software processing times ³ Using JPEG compression ⁴ Using TIFF CCITT Group 4 compression ⁵ Maximum capacity varies depending upon paper thickness ⁶ Selectable maximum density may vary depending on length of document ⁷ When scanning at high resolutions (600 dpi or higher), some limitations to document size may apply depending on system environment ⁸ Excludes ADF chute ⁹ Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for Linux and WIA Driver ¹⁰ Can be downloaded following instructions on Setup DVD-ROM ¹¹ PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency and RoHS requirements (2005/95/EC)



Insist on Genuine Fujitsu Service to keep your scanner running at its best

