Canon

imageRUNNER ADVANCE DX C7780i/C7770i C7765i

imageRUNNER ADVANCE DX C7700 Series

Print up to 80/70 ppm (BW/color)

Scan up to 270/270 ipm (300 dpi) (BW/color, duplex)

Print up to 13" × 19"

9,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE DX multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with pre-defined settings such as number of copies and finishing requirements.



- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*,² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control³ utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE DX models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

Color High-volume Multifunction



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT


- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR[®] certified and rated EPEAT[®] Gold.⁵

CONFIGURATION OPTIONS



Main Unit

Type

Color Laser Multifunctional

Core Functions Standard: Print, Copy, Scan, Send, Store Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

Standard: 10.1" TFT LCD WSVGA Color Touch-panel Optional: 10.4" TFT LCD WSVGA Color Upright-panel

Memory

4.0 GB RAM

Hard Disk Drive Standard: 250 GB/Maximum: 1 TB

Print Resolution

2400 dpi x 2400 dpi

Interface Connection

Network	
Standard:	1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
0-+:	
Optional:	NFC, Bluetooth Low Energy
Others	
Standard:	USB 2.0 (Host) x 1,USB 3.0 (Host)x 1,
	USB 2.0 (Device) x 1
Optional:	Copy Control Interface
optional.	copy control interface

Paper Capacity (LTR, 20 lb. Bond)

Standard:	3,550 Sheets
Maximum:	9,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard:	Two 1,100-sheet Paper Drawers,
	Two 550-sheet Paper Cassettes,
	250-sheet Multi-purpose Tray
Optional:	3,660-sheet Paper Deck (Paper Deck
	Unit-E1), 3,660-sheet Paper Deck (POD Deck
	Lite-C1), 6,000-sheet Paper Deck (Multi-
	Drawer Paper Deck-C1)
Maximum:	9,300 Sheets (With Multi-Drawer Paper Deck-C1)

Paper Output Capacity (LTR, 20 lb. Bond)

250 Sheets (with Copy Tray-R2)

4,250 Sheets (with Staple Finisher-X1 or Booklet Finisher-X1)

Finishing Capabilities

With Finishers:	Collate, Group, Offset, Staple, Saddle-Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold, Double Parallel-fold, Trimming
	Trimming

Supported Media Types

capper tea meana rypes	
Multi-purpose	Thin, Plain, Recycled, Color, Heavy, Coated,
tray:	Textured, Tracing, ⁶ Bond, Transparency,
	Label, Pre-punched, Letterhead, Tab,
	Envelope
Paper Decks:	Thin, Plain, Recycled, Color, Heavy, Tracing,
	Bond, Transparency, Bond, Pre-punched,
	Letterhead
Paper	Thin, Plain, Recycled, Color, Heavy, Bond,
Cassettes:	Transparency, Pre-punched, Letterhead,
	Tab. Envelope ⁷

Supported Media Sizes

Multi-purpose Tray:	Standard size: 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size/Free Size: 4" x 5-7/8" to 13" x 19-1/4", Envelope: COM10 No.10, Monarch, DL, ISO-C5, Envelope Custom Size: 3-1-/2" x 5-7/8" to 13" x 19-1/4"
Paper Decks: Paper Cassettes:	Letter 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size: 5-1/2" x 7-1/8" to 13" x 19-1/4", Envelope: COM10 No.10, Monarch, DL, ISO-C5, Envelope Custom Size : 3-7/8" x 5-7/8" to 13" x 19-1/4"

Supported Media Weights

Paper Drawers: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) Paper Cassettes:14 lb. Bond to 140 lb. Index (52 to 256 g/m²) Multi-purpose 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²) Tray:

14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) Duplexing: Print/Copy Speed (BW/Color)

C7780i:	Up to 80/70 ppm (Letter); Up to 60/52 ppm (Letter-R); Up to 47/41 ppm (Legal);	
C7770i:	Up to 40/35 ppm (11" x 17") Up to 70/65 ppm (Letter); Up to 52/48 ppm (Letter-R); Up to 41/38 ppm (Legal);	
C7765i:	Up to 35/32 ppm (11" x 17") Up to 65/60 ppm (Letter); Up to 48/45 ppm (Letter-R); Up to 38/35 ppm (Legal); Up to 32/30 ppm (11" x 17")	
Warm-up Time		
From Power On: Quick Startup	Approx. 30 Seconds ⁸	
Mode: From Sleep	Approx. 4 Seconds ⁹	
Mode:	30 Seconds or Less ¹⁰	
Dimensions (W x D x H) 27-1/8" x 36-7/8" x 46-5/8" (689 mm x 937 mm x 1,185 mm)		
Installation Space (W x D)		

Basic: 79-3/4" x 60" (2 026 mm x 1 524 mm) (with front cover open + Multi-purpose tray/upper-right cover open + Buffer Pass+ Booklet Finisher-AC1/extension tray and rotary tray extended)

Fully Configured: 150-3/8" x 60" (3,818 mm x 1,524 mm) (with front door open + Multi-Drawer Paper Deck-C1 + Buffer Pass + Document Insertion Unit-N1 + Multi Function Professional Puncher-B1 + Paper Folding Unit-J1+ Booklet Finisher-X1) Weight

Approx. 562.2 lb. (255 kg)

Print Specifications

Data Processing Resolution (dpi) 2400 x 2400

Standard Page Description Languages UFR II, PCL®6, Adobe® PS® 3

Supported File Types for Direct Print PDF, TIFF, JPEG, EPS,12 XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Universal Print by Microsoft[®], Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information. Fonts

РίΙ	•	

PCL:	93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese,	
	Korean, Simplified and Traditional Chinese), ¹³	
	Barcode Fonts ¹⁴	
PS:	136 Roman	
Operating System ¹⁵		
UFR II/PS:	Windows® 7/8.1/10/Server2008/	

	Server2008 R2/Server2012/Server2012
	R2/Server2016/Server2019, Mac OS X(10.10
	or later)
PCL:	Windows 7/8.1/10/Server2008/Server2008
	R2/Server2012/Server2012 R2/
	Server2016/Server2019
PPD:	Windows 7/8.1/10, Mac OS X(10.9 or later)

Copy Specifications

First-Conv-Out Time (Letter)

·	
C7780i :	As fast as 4.4 seconds (BW)/
	5.4 seconds (Color)
C7770i:	As fast as 4.8 seconds (BW)/
	5.9 seconds (Color)
C7765i:	As fast as 4.8 seconds (BW)/
	5.9 seconds (Color)

Copy Resolution (dpi)

 600×600

Multiple Copies

Up to 9,999 Magnification

25%-400% (1% Increments)

Preset Reduction/Enlargement

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder Document Feeder Paper Capacity

200 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" x 5-1/2" to 12"x 17

Document Feeder Supported Media Weights

Single-sided/Double-sided Scanning: 13.3 lb. Bond to 80 lb. Cover (50 to 220 gsm)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

Pull Scan

Color Network ScanGear2 for both Twain and WIA Supported OS: Windows/7/8.1/10 Server 2008/Server 2008 R2/Server 2012/

Server 2012 R2/Server 2016

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning BW/Color: 135/135 ipm (300 dpi), 80/80 ipm (600 dpi)

. Double-sided Scanning

BW/Color: 270/270 ipm (300 dpi), 160/90 ipm (600 dpi)

Send Specifications

Destination Standard:

E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box Super G3 FAX, IP Fax Optional

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

Up to 600 x 600 Push: Up to 600 x 600 Pull:

Communication Protocol

File:	
Email:	

FTP (TCP/IP), SMB v3.0, WebDAV SMTP, PÓP3

File Format Standard:

TIFF, JPEG, PDF (Limited Color, Compact, Searchable, Apply Policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications (Optional)

Maximum Number of Connection Lines

Modem Speed Super G3: 33.6 Kbps

63 14.4 Kbps **Compression Method**

MH, MR, MMR, JBIG Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100 Sending/Recording Size

Statement-R to 11" x 17

Fax Memory Up to 30,000 Pages (2,000 Jobs) Speed Dials

Max 200 Group Dials/Destinations Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

Yes

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 10,000 Pages (2,000 Jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 8.1/10) Concurrent Connections (Max.) SMR 64 WebDAV

Advanced Box Available Disk Space

Approx. 16 GB (Standard HDD)/Approx. 480 GB

Security Specifications

Authentication

Universal Login Manager, uniFLOW Online Standard-Express,¹⁶ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup,³ McAfee Embedded Control³ Hard Disk Drive Mirroring, IEEE 2600.2 Optional: Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network Standard

Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEÈ 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document Standard

Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signature

Environmental Specifications

Operating Enviornment

Temperature: 50 to 86 °F 20 to 80% RH (Relative Humidity) . Humidity:

Power Requirements

208 - 240 V AC. 60 Hz.12 A C7780i: C7770i/C7765i: 110-127 V AC, 60 Hz,16 A

Power Consumption

Maximum C7780i: Approx. 2,500 W C7770i/7765i: Approx. 2,000 W Standby¹⁷ C7780i: Approx. 126.3 W C7770i/C7765i Approx. 119.2 W Approx. 0.9 W¹⁸ Sleep Mode: Typical Electricity Consumption (TEC) Rating¹⁹ C7780i: C7770i: 1.39 kWh 1.23 kWh C7765i 1.18 kWh Standards

ENERGY STAR® Certified Rated EPEAT® Gold⁵

Consumables

Toner GPR-56 Toner

Toner Yield (Estimated @ 5% Coverage)

- Black 82,000 Images Color (C,M,Y): 66,500 Images
- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.
 ² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure
- compatibility with all third-party SIEM systems. ³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.
- Requires additional option.
- ⁵ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- ⁶ Some types of tracing paper cannot be used.
 ⁷ Envelope Attachment-F1 required.
- ⁸ Time from device power-on, until copy ready (not print reservation).
- ⁹ Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display. ¹⁰ Time from exiting Sleep mode to when printing is operational.
- " Includes main unit, ADF, and consumables. ¹² EPS can be printed directly only from the Remote User
- Interface. ¹³ Requires the optional PCL International Font Set-A1.
- 14 Requires the optional Barcode Printer Kit-D1
- ¹⁵ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁶ No charge for this solution; however, activation is required. ¹⁷ Reference Value: measured one unit.
 ¹⁸ 0.9 W Sleep mode is not available in all circumstances
- due to certain settings. ¹⁹ Based on ENERGY STAR Product Specification for Imaging
- Equipment Version 3.0.

2000



As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output An other referenced product names and marks are trademarks of their respective owners. An primer output images are simulated. All features presented in this brochurer may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for

USA.CANON.COM/SIMPLYADVANCED

typographical errors. ©2020 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.







To learn about Canon's many awards, visit usa.canon.com/awards.