

TOSHIBA

e-STUDIO3525AC/4525AC

- High-Speed – Up to 35 & 45PPM
- Compact Design
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



MAIN SPECIFICATIONS

Copy System	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	35/45 PPM (LT)
First Copy Out	Color: Less Than 7.8/5.7 Seconds Monochrome: Less Than 5.9/4.4 Seconds
Warm-Up Time	From powering on: Approx. 20 Seconds From Sleep & Low Power: Less Than 12 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard: 550 Sheets/Max. 5,200 Sheets
Original Feed	300-Sheet DSD/ or DSD/ with Double Feed Detection or 100-Sheet RADF
Scan Speed & Weights	DSD/ Scan: 70IPM (Monochrome or Color), Simplex or Duplex: 9.3-110lb Bond RADF Scan: 50IPM (Monochrome or Color), Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
Max. Original Size	LD/A3
Paper Feed Sizes	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-110lb Cover Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-140lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-28lb Bond Opt. 2,000-Sheet External LCF-LT 16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Paper Weights	25% to 400% Max. 105K Month (Color: 100%) Max. 210K Month (Monochrome: 100%) Approx.169lb/172lb 23" (W) x 25.2" (D) x 31" (H) CMY: 38K, K: 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 4GB 128GB Solid State Drive (SSD)
Duplex	
Reproduction Ratio	
Max Duty Cycle	
Weight	
Approx. Dimensions	
CMYK Toner Yield	
Power Source	
Power Consumption	
Plug Type	
Memory	
Hard Disk Drive	

e-BRIDGE NEXT PRINT SPECIFICATIONS

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1,10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Network Protocols	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
Printing Protocols	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Print Drivers	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Interface	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Wireless Device	TopAccess
Device Management	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Account Control	
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

Scan Speed	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color) Standard: Full Color, Auto Color, Monochrome, Grayscale DOC/XLS/PPT/PDF
Scan Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
OCR	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX, Color/Grayscale: JPEG, TIFFMulti/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF, XPSMulti/Single Page, DOCX, XLSX, PPTX
Scan Resolution	Color/Grayscale: JPEG (High, Middle, Low)
File Formats	
Image Compression	

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-FILING SPECIFICATIONS

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

ACCESSORIES (OPTIONS)

Platen & Document Feeder Options		IPSec Enabler	GP1080NODE
DSD/	MR4010	Unicode Font Enabler	GS1007NODE
DSD/ with Double Feed Detection	MR4020	Multi-Station Print Enabler	
RADF	MR3033	Per Seat License	GS1090NODE
Platen Cover	KA5005PC	e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Additional Paper Options		e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
Paper Feed Pedestal	KD1072	e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
Drawer Module	MY1052	e-BRIDGE Plus for Gmail	GB2380NODE
Envelope Cassette Option	MY1053	e-BRIDGE Plus for Google Workspace	GB2390NODE
Large Capacity Feeder	KD1073LT	Hardcopy Security Printing	GP1190NODE
External Large Capacity Feeder	MP2002	Security SSD (512GB)	GE1280
Finishing Options		FIPS HDD (320GB)	GE1260
50-Sheet Inner Finisher	MJ1048	e-BRIDGE Plus Voice Guidance	GB2540NODE
65-Sheet Staple Finisher	MJ1113	e-BRIDGE Global Print	GB2550NODE
65-Sheet Saddle-Stitch Finisher	MJ1114	Miscellaneous Options	
Hole Punch for MJ1048	MJ6011	Card Reader Holder	GR1320
Hole Punch for MJ1113/MJ1114	MJ6107	Accessory Tray	GR1330
Bridge Kit	KN5005	Panel 10-Key Option	GR1340
Job Separator	MJ5015	Stand	STAND5015
Connectivity/Security Options		Work Tray	KK5005
FAX Unit/2 nd Line for FAX Unit	GD1370N	Manual Pocket	KK5008
Wireless LAN/Bluetooth	GN4030A3	Harness for Coin Controller	Q1280
Fax Over IP License Key	GS1100NODE	Accessible Arm	KK2560
Bluetooth Keyboard	GR9001		
2 nd NIC Holder	GR1430		
USB Hub	GR1420		
Meta Scan Enabler	GS1010NODE		

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

www.business.toshiba.com