

- > Industrial 4" Thermal Label Printer
- > Low Cost of Operation
- > Designed for Scalability and Flexibility
- > Low Maintenance
- > Energy Star Certified



> **B-EX4T2**



**STANDARD FEATURES**

- > Flat edge print head design
- > Thermal transfer or direct thermal
- > Models in 200 dpi, 300 dpi, 600 dpi
- > 32MB DRAM, 16MB Flash
- > Dual ribbon motor
- > Ribbon capacity – 600 meter
- > Maximum speed - 12 ips
- > ZPL II® emulation
- > ENERGY STAR certified
- > Long head life – 3 million linear inches¹
- > Snap-in user upgradeable print heads
- > XML enabled Printing
- > Rugged metal construction

KEY SELLING FEATURES**Performance Leader**

- Best in class print speed, large DRAM & flash memory
- High reliability designed for industrial printing

Low TCO (Total Cost of Operation)

- Dual Ribbon Motor System
 - Ensures better ribbon handling
 - Eliminates ribbon wrinkling or unusable, unscannable labels
- Long-lasting print head
 - Supports up to 3 million linear inches¹
 - Less user intervention and print head replacement cost
- Large 600 meter ribbon
 - Minimize user intervention
- ENERGY STAR
 - Low energy consumption in idle and print mode
 - Substantial energy and cost savings

Flexibility

- User installable snap-in print heads
 - 200 to 300 dpi interchangeable print heads without tools
 - Auto print head detection
 - Easy service and maintenance
- Emulation Technology
 - ZPL II® emulation standard
 - Seamless integration into existing environments
- Scalable with RFID upgradability²
 - Protect investment and support RFID growth initiatives

Ease of Use

- Easy ribbon and media loading
 - Designed for single step loading without threading or multiple steps
 - Ensures maximum uptime
- Network Printer Management Tool
 - Monitor and control printers from desktop

Environmental

Operating Temperature	40°F -104°F (5°C - 40°C)
Operating Humidity	25 - 85 % RH (non- condensing)
Power Consumption	Printing Mode: 116W, .59A Stand-By Mode: 15W or less Sleep Mode: 5.7W, .09A
Physical Dimensions (W x H x D)	10.9" x 12.2" x 18.11" (278 mm x 310mm x 460mm)
Weight	36.7 lbs./17 kg
Weight Shipping	41.9 lbs./19Kg

Models

B-EX4T2-GS (200 dpi), B-EX4T2-TS (300 dpi), B-EX4T2-HS (600 dpi),
B-EX4D2-GS (200 dpi Direct Thermal)

Printer Specifications

Technology	Thermal transfer/ Direct thermal
Resolution	200 dpi (8 dots/mm), 300 dpi (11.6 dots/mm)
Print Speed (Maximum)	200 dpi: 12 ips (300 mm/sec), 300 dpi: 12 ips (305 mm/sec), 600 dpi: 6 ips (152 mm/sec)
Memory	DRAM - 32MB, Flash - 16MB
Graphic Display	128 x 64 pixel
Print Length	58.9"
Print Width	4.09"(104 mm)

Media

Ribbon Length	600M
Ribbon Core Diameter	1.01" ± 0.008" (Ø25.7± 0.2mm)
Ribbon Outer Diameter	3.45" (90mm)
Media Sensors	Adjustable reflective (Black Mark) Adjustable transmissive (Gap, Notch, Hole) Disable (Continuous media)
Media Length	.31"-58.9" (8.0mm – 1498mm)
Media Width	.98"-4.72" (25.0mm – 120mm) (including backing)
Media Thickness	Label: .003"- .007" (.08mm - .17mm) Tag: .003"- .010" (.08mm - .263mm)
Programming Languages	TPCL (TOSHIBA Print Command Language) ZPL (Zebra Programming Language)
Interfaces Standard	USB 2.0, Ethernet
Interfaces Optional	Wireless or Serial, Parallel, Expansion I/O, RTC (real time clock) and USB
Options and Accessories	Disc cutter Peel off with liner rewind Partial roll rewind (internally rewinds) RFID (UHF)Module 300 dpi thermal head
Bar Code Symbologies	
Linear Bar Codes:	JAN8, JAN13, EAN8, EAN8+2 digits, EAN8+5 digits, EAN13, EAN13+2 digits, EAN13+5 digits, UPC-E, UPC-E+2 digits, UPC-E+5 digits, UPC-A, UPC-A+2 digits, UPC-A+5 digits, MSI, ITF, NW-7, CODE39, CODE93, CODE128, EAN128, Industrial 2 to 5, Customer Bar Code, POSTNET, KIX CODE, RM4SCC (ROYAL MAIL 4 STATE CUSTOMER CODE), GS1 DataBar
2 – Dimensional:	Data Matrix, PDF417, QR code, Maxi Code, Micro PDF417, CP Code

**Corporate Office**

2 Musick, Irvine, CA 92618-1631

Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-3136-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

West Coast

142 Technology, Suite 150, Irvine, CA 92618

Tel: 949-462-6262

Web Site

www.business.toshiba.com