

Xerox® DocuMate® 4799 Versatile High-Speed Scanner Provides Extra Performance for Heavy Scanning Demands

- 112 ppm / 224 ipm* at 300 dpi
- A3 (11" x 17") paper size
- ADF holds 350 pages[†]
- 3 Ultrasonic double feed detection sensors
- Create searchable PDF files to make it easy to find scanned documents
- Pre- & Post-Scan Imprinter (sold separately)
- Color Space Compatibility with Xerox[®] iGen[®] Digital Press
- Xerox® FreeFlow Makeready® Supported
- * Landscape A4, b&w, gray & color.
- + 20 lb., 75-80 g/m² paper



Overcome Your Fear of Difficult Documents

Versatility, high-speed and superior reliability make the Xerox® DocuMate® 4799 a powerful scanner for demanding environments. With up to a 40,000 page per day duty cycle, this innovative workhorse scans up to 112 pages per minute and employs three advanced sensor systems: ultrasonic double feed detection, stapled document detection and intelligent feed control to ensure that your scan job will not get interrupted.

Documents of various sizes can be stacked together in the automatic feed tray without worry because the Xerox® DocuMate® 4799 employs not one, but three ultrasonic double feed detection sensors to cover the entire width of a document. The scanner has another set of sensors designed to detect staples anywhere in a document. As soon as a staple is detected, the scanning process is halted—minimizing damage to the optical glass and your documents. A third set of sensors constantly monitors the thickness of documents being fed into the scanner and automatically adjusts the roller pressure to ensure that all pages are accurately fed. This combination of sensors creates one of the most reliable feed mechanisms available today.

Up to 350 mix-sized documents can be stacked in the center of the automatic feeder. There is no need to organize documents according to their size, so scanning is fast, easy and

efficient. A pre- and post-scan imprinter is also available for the Xerox® DocuMate® 4799 and is supported through the included TWAIN™ and ISIS® drivers.

Advanced Image Processing Technology

The Xerox® DocuMate® 4799 provides both high quality image enhancement and increased productivity with Kofax® VRS™ Professional AIPE-EBC for auto-everything scanning, including Auto Rotation, Blank Page Deletion and Auto Color Detect. VRS Professional improves your workflow and reduces the total time needed to scan even the largest volumes of mixed batch documents. Taken together, the Xerox® DocuMate® 4799 and the Kofax VRS Professional bundle translate into real and measurable savings—fewer manual steps, reduced storage requirements and less operator intervention.

When the occasional paper jam happens, the Xerox® DocuMate® 4799 is very easy to maintain. Its unique "clamshell" design allows full access to the entire paper path, so you can clear paper jams or clean the unit without calling a service technician. The rollers are easy to replace, improving the unit's cost effectiveness, and have a long service life.

Designed for document capture and workflow the Xerox® DocuMate® 4799 is everything you ever wanted in a high-speed document scanner: productivity, reliability and innovation.

Xerox® DocuMate® 4799 Software Solutions

XDM47995D-WU

XDM47995E-WU

XDM47995E-VRS/B

Dual Color CIS detector

Xenon Lamp

600 dpi

Automatic Document Feeder (ADF)

Switchable black or white background

Hi-speed USB 2.0 (1.1 compatible)

1.9" x 2.8" (48 mm x 70 mm)

24-bit color, 8-bit grayscale, 1-bit black & white

Up to 350 sheets (20 lb., 75-80 g/m² paper)

Normal mode: 13 - 42 lbs. (50 - 157 g/m²)

Thick mode: 42 - 56 lbs. (157 - 209 g/m²)

Auto mode: 5 - 42 lbs. (20 - 157 g/m²)

Note: 1 mil = 0.001"

AC 100 - 240 V, 50/60 Hz

150 watts while scanning

5.3 watts or less in Sleep Mode

Temperature: 59°F - 86°F (15°C - 30°C)

Temperature: 32°F - 104°F (0°C - 40°C)

18.7"(w) x 23"(d) x 13"(h) (474 x 585 x 329 mm)

70 watts on standby

Humidity: 10 - 80 % RH

Humidity: 30 - 80 % RH

40,000 pages/day

Thin mode: 5 - 13 lbs. (20 - 50 g/m²)

Length control, barcode detection, patch code detection,

DocuMate 4700 flatbed scanner, Pre- & Post-Scan Imprinter

11.9" x 17" (302 × 432 mm); custom lengths up to 100" (2540 mm)

1.9 - 7.9 mils (0.04 - 0.2 mm) Straight path: max. 23.6 mils (0.6 mm)

Ultrasonic double feed detection (3 positions), stapled document detection

Automatic separation, control sheet, long paper mode

XDM47995D-VRS/B

Image Enhancement Technology

Visioneer® OneTouch® is integrated with image enhancing software such as Visioneer Acuity with DriverPLUS or Kofax® VRS™ (VirtualReScan), model dependent. Using advanced algorithms and dynamic thresholding, these software tools effectively improve the visual clarity of every document that you scan, applying intelligent correction to imperfect images, increasing OCR accuracy, and saving time.

Xerox® DocuMate® 4799 Product Specifications

Model Number w/VRS Pro (US)

Scan Speed

Scan Method

Light Source

Background

Imaging Sensor

Optical Resolution

Output Bit Depth

Other Functions

Interface

Detection

Accessories

ADF Capacity

Document Weight

Document Thickness

Power Requirement

Power Consumption

Operating Environment

Storage Environment

Dimensions

Weight

Duty Cycle

ADF Minimum Document Size

ADF Maximum Document Size

Model Number w/VRS Basic (US)

Model Number w/VRS Pro (Euro/UK)

Model Number w/VRS Basic (Euro/UK)

Nuance® Searchable PDF Solution

Nuance OmniPage® and PDF Converter provide everything you need to create, convert, edit, assemble and securely share searchable PDF files with precision OCR analysis, advanced layout detection and Logical Form Recognition™ (LFR) technology. Combining powerful functionality, superior Microsoft® Office® support and DMS integration into one package.

112 ppm / 224 ipm (color, grayscale, or b&w @ 150, 200, or 300 dpi, landscape A4)

Office Gemini Diamond Vision

Diamond Vision production scanning software provides all the features required for document capture, processing and reporting. It allows businesses both large and small to easily convert their scanned documents into digital files, capture images and information contained in them, and then organize it all into searchable data. This mission-critical business information is then placed into a centralized location to be easily searched, stored and retrieved when needed.

Box Contents

- DocuMate 4799 Scanner
- Quick Installation Guide
- Technical Support Card
- Blower w/Brush
- Roller Cleaning Paper, Cleaning Paper Card
- Shading Sheet, Shading Caution Leaflet
- DFP (Double Feed Protection) Roller
- AC Power Cord US (1), Euro/UK (2)
- USB Cable
- DVD-ROM including:
 - User's Manual
 - Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU
 - Nuance® OmniPage® Pro
 - Nuance PDF Converter
 - Office Gemini Diamond Vision
 - Visioneer OneTouch
 - Visioneer Acuity
 - Scanner Drivers: TWAIN™, EMC Captiva ISIS®, Microsoft® Windows® Image Acquisition (WIA) Driver

PC Minimum System Requirements

- Intel® Pentium® 4 or equivalent processor
- Windows 8 / 7 / Vista® / XP®
- 2GB RAM
- 350 MB available hard disk space
- DVD-ROM drive
- USB port

Warranty Information

- Standard 90-Day Warranty
- Optional 1-5 year Advanced Exchange
- Optional 1-5 year Next Day Business *
- Optional 1-5 year 4-hour response *

Consumables:

• 4799ROLL-KIT - User installable roller assembly. Roller kits last up to 400,000 scans, depending on scanning conditions.

For more information about the Xerox line of scanners, visit www.xeroxscanners.com















55 lbs. (25 kg)











*Includes 1 preventive maintenance visit per year. Coverage is available Monday through Friday 8:00 am to 5:00 pm (local time), excluding US holidays.

©2013 Xerox Corporation. All rights reserved. Xerox@, Xerox and Design@, DocuMate@, FreeFlow Makeready@ and iGen@ are trademarks of Xerox Corporation in the United States and/or other countries. Visioneer@ and Visioneer OneTouch@ are trademarks of Visioneer, Inc. Kofax@, VirtualReScan@ and VRS™ are trademarks of Kofax, Inc. Nuance@ and OmniPage@ are trademarks of Nuance Communications, Inc. or its affiliates in the United States and/or other countries. Diamond Vision@ is a registered trademark of Office Gemini. Microsoft@, Windows Vista@, Windows@, the Windows logo and XP@ are trademarks of Microsoft Corporation in the United States and/or other countries. Intel@ and Pentium@ are trademarks of Intel Corporation in the U.S. and/or other countries. TWAIN™ is a trademark of TWAIN Working Group. EMC@, Captiva@, and ISIS@ are trademarks of EMC Corporation. Universal Serial Bus is a trademark of USB Implementers Forum, Inc. (USB-IF). All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox products and services are subject to change without notice. 10/13

