



POWERFUL PERFORMANCE, ENHANCED OPERABILITY, ENERGY EFFICIENCY



FULL-COLOR LEDGER-SIZE WORKGROUP DOCUMENT SYSTEMS

Sharp's new MX-2640N/3140N/3640N color series document systems combine the simplicity of touch-screen menu navigation with robust multi-tasking workflow features that can help virtually any office accomplish more in less time. A large 10.1" (diagonally measured) high-resolution, tilting touch-screen display offers groundbreaking real-time image preview with intuitive flick-and-tap editing to help ensure your documents are produced accurately and without waste. This new series also offers many advanced features such as a fully customizable home screen, dynamic action menus that provide feature-specific guidance, and a full-size retractable keyboard for easy data entry. Plus, with Pantone® licensing, these models offer unprecedented levels of color fidelity – combined with true 1200 x 1200 dpi print resolution, they can help your business produce professional-looking color documents in-house with breathtaking image quality that is also economical. The new MX-2640N/3140N/3640N color series has been built on the latest Sharp OSA® development platform, making integration with network applications and cloud services easier than ever. And with Sharp's industry-leading security platform with standard 256-bit data encryption and overwrite protection, you can rest assured that your intellectual property is well protected.

Advanced features plus multi-functional capability allow you to meet tomorrow's document needs today.

- Large 10.1" high resolution touch-screen display with tilt view
- Real-time image preview feature with flick, tap and slide navigation, and multi-touch pinch-andzoom capability to shrink and enlarge images
- Fully customizable home screen feature enables users to add custom backgrounds and icons, change the display language and more
- New 500 + 2,000-sheet tandem paper drawer option expands maximum online paper capacity to 6,600 sheets

- Pantone Licensing offers unprecedented levels of color fidelity to the PANTONE MATCHING SYSTEM®
- 1200 x 1200 dpi printing provides clear, crisp images even on jobs with fine detail
- Industry-leading ImageSENDTM function scans both black and white and color documents at up to 50 images per minute to USB devices, network folders, E-mail and more
- Network ready PCL®6 and true Adobe®
 PostScript®3™ printing systems with direct print function and available XPS option
- Easy-to-use Document Filing System with thumbnail view and image preview features for easy identification
- Supports the latest Sharp OSA development platform, enabling businesses to easily integrate with network applications and cloud services

- Flexible paper handling system feeds up to
 80 lb cover through the paper trays and up to
 110 lb cover through the bypass tray
- Super G3 fax option with intelligent inbound routing to multiple destinations
- Supports Sharp's award-winning security platform with standard 256-bit data encryption and up to 7 times overwrite protection
- Energy efficient belt fusing system offers low power consumption, fast warm up and enhanced print quality



MX-2640N/MX-3140N/MX-3640N SPECIFICATIONS

Main Specification	IS						
MX-2640N/	Base models in	nclude	multi-tasking	contro	ller, high-r	resolutio	n touch-
3140N/3640N	screen display,						
	document filing, PCL®6 and Adobe® PostScript® 3™ printing systems, network printing, network scanning, duplexing, 500-						
	paper drawer,						
Type	Console, color						
Display	10.1" (diagona						na display.
	1024 x 600 do						. ,
Functions	Copy, print, net						
Copy System	Dry electrostati						
Originale	brush developm			t type f	using/whit	e LED ex	kposure
Originals Max Original Size	Sheets and bou	ına aoc	cuments				
Copy Size	Min. 5½" x 8½	" Max	11" x 17" +	12" x	18"		
Copy Speed	26/31/36 ppm						
Multiple Copy	Max. 999 copie	es					
First Copy Time		MX-20		MX-3		MX-3	
(Seconds) ²		Black		Black		Black	
	Platen Glass Doc. Feeder	5.9 9.1	8.1 11.6	5.8 9.1	7.9 11.6	5.2 8.1	6.8 10.6
Warm Up Time	18 seconds or		11.0	9.1	11.0	0.1	10.0
Magnification	25% to 400%		ncrements (w	ith doc	ument fee	der 25%	-200%)
Original Feed	100-sheet RSP						
Scan Speed	Copy mode: up	to 50 (OPM (B&W) @			up to 36	6
	OPM (Color) @						
Original C'	Network scan:						:
Original Sizes Paper Feed	5½" x 8½", 8½						tomont)
System	Standard: (1) 5 and 100-sheet						
Oyotom	Optional: single						
	drawer), tanden						
Paper Types	Paper drawers:	16 lb.	bond to 80 II	o. cove	r. Other pa	per type	s include
	plain, pre-printe						
	Bypass tray: 16						
	110 lb. cover (h						
	tab paper (letter). Also label paper, gloss paper, pre-printed, recycled, pre- punched, letterhead, color paper and OHP film.						
Duplexing	Standard auton						
CPU	Up to 1.8 GHz						
Interface	RJ-45 Ethernet			-T), US	B 2.0 (2 h	ost ports	s, front and
	rear), USB 2.0						
Memory Hard Disk Drive	Standard 4 GB 320 GB; 105 (na			
Copy Resolution	Scan: B&W/cold				rt· R&W/col	lor: 600:	600 dni
Color Modes	Auto Color Con						
Exposure	Modes: Automa						
Control	Photo, Map, Pa	le-Colo	r Document.	Setting	s: Auto or !	9 step n	nanual
Halftone	256 gradations						
Copy Features	Scan-Once Prir						
	Sensing (ACS), Auto Paper Sensing (APS), Auto Magnification Sensing						
	(AMS), image preview, image edit, auto tray switching, rotation copy, reserve copy, tandem copy, book copy, margin shift, tab-paper						
	reserve copy, tandem copy, book copy, margin shift, tab-paper insertion, edge erase, center erase, book divide, dual page copy, cover						
	pages, insert pages, OHP insertion, job build, card shot, blank page						
	skip, mirror image, black-white reversal, centering, proof copy, 2-in-						
	1/4-in-1/8-in-1, pamphlet, watermark custom image, job programs,						
	date/character/page stamp.						
Account Control	Up to 1000 users. Supports user-number authentication (on device), login						
	name/password (on device) or login name/password (on device via LDAP server) for copy, print, scan, fax and document management.						
Output Tray	Main output tra						t
Capacity	tray (right 1 sid				,,,		
Firmware	Flash ROM with				te capabilit	ty and fir	mware
Management	update 1 to N v						
Configuration	Web-based ma					el login,	cloning
Method	(1 to N) with SF					nd oliole	counte
Contino/Etion	Remote front panel, remote access to service logs and click counts						
Service/Functions	Tilt front panel, adjustment of key touch sound and speed, document feeder free stop, job programs, remote front panel, universal grip for						
Accessibility							
		o, job p	rograms, rem	ote fro			
Accessibility	feeder free stop	o, job p d disab	rograms, rem le screen tim	ote froi eout			
Accessibility Features Environmental Standards	feeder free stop paper trays, an International En	o, job p d disab ergy St	rograms, rem le screen tim ar Program V	ote froi eout er. 1.2			
Accessibility Features Environmental Standards Power	feeder free stop paper trays, an International En	o, job p d disab ergy St AC, 60	rograms, rem le screen tim ar Program V HZ, 12 Amps	ote froi eout er. 1.2			
Accessibility Features Environmental Standards	feeder free stop paper trays, an International En	o, job p d disab ergy St AC, 60	rograms, rem le screen tim ar Program V HZ, 12 Amps	ote froi eout er. 1.2			

Network Printing S	System
PDL	Standard PCL6 compatible, PostScript 3, optional XPS
Resolution	1200 x 1200 dpi
Print Speed	26/31/36 pages per minute (8½" x 11")
Print Drivers	Windows XP, Windows XP x64, Windows Server® 2003-2008,
	Windows Server 2003-2008 x64, Windows Vista®, Windows Vista x64,
	Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows
	Server 2012 x64, Windows PPD, MAC OSX® (including 10.4, 10.5,
	10.6, 10.7, 10.8), all MAC PPD
Features	Auto configuration, continuous printing, electronic sorting, offset
	stacking, N-up printing, duplex printing, transparency inserts, margin
	shift, image rotation, different cover page, poster print, job bypass print,
	job retention, confidential print, proof print, user authentication, image
	stamp and watermarks. Additional features: Multiple pamphlet, network
	tandem print, carbon copy print mode, different cover page/last
	page/other page, form overlay, tab paper settings, tab printing, chapter
	inserts, page Interleave and bar code font printing ¹
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, PostScript
	and XPS1; Methods: FTP, SMB, Web page, E-mail and USB memory
Resident Fonts	80 outline fonts (PCL), 136 fonts (PS)
Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0
Operating	Windows Server 2003-2008, Windows XP, Windows Vista, Windows
Systems	7, Windows 8, Mac OS X 10.4, X10.5, X10.6, X10.7, X10.8, Novell®
	inux® and Citrix® (XenApp 5.0, 6.0, 6.5) and
	ervices, SAP device types ¹
Network	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP,
Protocols	POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for Unix.
	IPX/SPX® for Novell environments. EtherTalk®. AppleTalk® for
Deletter	Macintosh® environments.1
Printing	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP, POP3, HTTP, and
Protocols Network	Novell Pserver/Rprinter
Security	IP/MAC address filtering, protocol filtering, port management, user authentication and document administration. ¹
,	IEEE-2600TM-2008, DoD (NSTISSP) #11, CAC/PIV access control ¹
occurry standards	ILLE-2000 HVI-2000, DUD (NS HSSE) #11, CAC/FIV access control
Network Scanning	System

Scan Modes	Standard: Color, monochrome, grayscale		
Max Original Size	11" x 17"		
Optical Resolution	600 dpi		
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi		
Image Formats	Monochrome: TIFF, PDF, PDF/A, Encrypted PDF, XPS		
	Color: Grayscale, Color TIFF, JPEG, PDF, Encrypted PDF, XPS		
	Internet Fax: TIFF-FX, TIFF-F, TIFF-S, PDF/A, Compact PDF1		
Image	Monochrome scanning: G3 (MH), G4 (MR/MMR)		
Compression	Color/grayscale: JPEG (high, middle, low)		
	Internet fax mode: MH/MMR (option)		
Scan Destinations	E-mail, Desktop, FTP, Network Folder (SMB), Home Directory, USB,		
	Internet fax (option), Super G3 fax (option)		
One-touch	Up to 2000 (combined scan destinations)		
Destinations			
Group Destinations	Up to 500		
Programs	48 (combined)		
Max. Jobs	Up to 100		
Network Protocols	TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB,		
	ESMTP and 802.1x.		
Network Security	E-mail server user authentication for LDAP and Active Directory		
Software	Sharpdesk® desktop document management software (1 user license) Sharpdesk Mobile		

Transmission	Super G3, G3
Mode	
Modem Speed	33.6 KBPS ³
Compression	JBIG, MMR, MR, MH
Methods	
Scanning Method	Sheet fed simplex or duplex or book
Max. Resolution	400 dpi
Transmit Speed	Approx. 2 seconds with Super G3/JBIG ⁴
Auto Dialing	Up to 2,000 (combined scan destinations)
Group Dial	Up to 500 destinations
Inbound Fax	Forwards received fax data to E-mail, FTP, SMB, Desktop, Fax, I-Fax1
Routing	
Long Length	Up to 33 1/4" (for transmission)
Originals	
Programs	48 (combined)
Memory	Shared
Halftone	256 levels

Saddle Stitch Fini	sher (option)
Туре	Console finisher with dual exit trays (mounts on left side
	of host machine)
Output Trays	Upper tray: Offset stack tray
	Lower tray: Book tray for saddle stitch
Output Capacity	1000 sheets (letter/statement size) or 500 sheets (legal, ledger
	or letter-R size)
Stapling	Up to 50 sheets (letter/statement) or 25 sheets (legal, ledger or mixed)
Output Delivery	Face down
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or both
Saddle Stitch	Center stitch/center folding (2 staples) letter/legal/ledger
Function	paper sizes
Saddle Stitch	Up to 10 sets (11-15 sheets per set)/15 sets (6-10 sheets per set)/
Max. Sets	20 sets (1-5 sheets per set)
Power	70 W or less (supplied from main unit)
Consumption	
Hole Punching	Optional hole punch unit MX-PNX5B (2 holes/3 holes)
Weight	Approx: 88 lbs.
Dimensions	26" (w) x 25" (d) x 39" (h) (with tray extended)

Inner Finisher (op	tion)
Туре	Built-in finisher (hole punch unit option)
Output Capacity	500 sheets (letter/statement) or 250 sheets (ledger/legal size)
Output Delivery	Face down
Stapling Media	Plain paper (letter, legal, or ledger size)
Stapling Positions	1 front, 1 rear, or both
Power	50 W or less (supplied from main unit)
Consumption	
Stapling	Up to 50 sheets (letter size) or 30 sheets (legal, ledger or mixed)
Stapled Sets	30 bundles or 500 sheets (letter or statement size) or
	30 bundles or 250 sheets (legal or ledger size)
Hole Punching	Optional hole punch unit MX-PN11B (2 holes/3 holes)
Weight	Approx. 26.5 lbs.
Dimensions	24¾" (w) x 23½" (d) x 8" (h) (includes extended tray)

Optional Equipme	ent
MX-DE12	Stand/1 x 500-sheet Paper Drawer
MX-DE13	Stand/2 x 500-sheet Paper Drawer
MX-DE14	Stand/3 x 500-sheet Paper Drawer
MX-DE20	Stand/500 + 2,000-sheet Tandem Paper Drawer
MX-LT10	Long Paper Feeding Tray
MX-36ABD	Rolling Cabinet Base
MX-LC11	Large Capacity Tray
MX-FN17	Inner Finisher
MX-PN11B	3 Hole Punch Unit (Requires MX-FN17)
MX-SCX1	Staple Cartridge (MX-FN17)
MX-FN10	Saddle Stitch Finisher
MX-RB10N	Paper Pass Unit (Required for MX-FN10)
MX-PNX5B	3 Hole Punch Unit (MX-FN10)
AR-SC3	Staple Cartridge (MX-FN10)
MX-TR13N	Right-side Exit Tray Unit
MX-TU12	Center Exit Tray Unit
MX-PUX1	XPS Expansion Kit (Requires MX-SHP2GBXPS)
MX-SHP2GBXPS	2GB Memory Upgrade (Required for MX-PUX1)
MX-FX11	Fax Expansion Kit
MX-FWX1	Internet Fax Kit
MX-PF10	Bar Code Font Kit
AR-SU1	Stamp Unit (Requires AR-SV1 Stamp Cartridge)
AR-SV1	Stamp Cartridge
MX-EB11	Enhanced Compression Kit
MX-EB12N	Mirror Expansion Kit
MX-AM10	Web Browsing Expansion Kit (Standard on the MX-3640N)
MX-AMX1	Application Integration Module
MX-FR41U	Commercial Data Security Kit
MX-EC50	CAC Reader (Requires Data Security Kit)

DVENDFS	Generic Vendor Interface Kit		
Supplies			
MX-36NTBA	Black Toner Cartridge		
MX-36NTCA	Cyan Toner Cartridge		
MX-36NTMA	Magenta Toner Cartridge		
MX-36NTYA	Yellow Toner Cartridge		
MX-36NVBA	Black Developer		
MX-36NVSA	Cyan/Magenta/Yellow Developer		
MX-36NRSA	Drum		
MX-230HB	Toner Collection Container		

Approx. Dimensions 24" (w) x 27" (d) x 33" (h)
















Design and specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows, Windows Server and Windows Vista are trademarks or registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.



¹ Some features require optional equipment. See your local dealer. ² May vary depending on product configuration, machine settings

and operating and/or environmental conditions.

3 Actual transmission time will vary based on line conditions.

4 Based on Sharp Standard Test Chart with approximately 700