



KONICA MINOLTA

TECHNOLOGY



bizhub® 3622

MONOCHROME ALL-IN-ONE PRINTER

Superior all-in-one functionality at up to 38 ppm in high-resolution B&W
50,000 page monthly volume for handling large workloads
900 sheet maximum paper capacity in small footprint
Standard Super G3 fax to give you more input/output capability

Scanning in both B&W and color with auto document feeder
Built-in PCL and PostScript productivity right out of the box
Mobile printing support
Standard wireless connectivity

bizhub 3622

MONOCHROME ALL-IN-ONE PRINTER

With fast 38 ppm print/copy output in high-resolution B&W, the bizhub 3622 can speed the flow of information with standard PCL and PostScript printer emulations and wireless connectivity, standard fax capability and simple operation — an ideal all-in-one solution for branch offices, small businesses, nurses' stations, schools, legal providers and retail locations.

SYSTEM OVERVIEW

System memory	1 GB
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet, USB 2.0, 802.11 wireless
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Automatic document feeder	Up to 50 originals / 4" x 6" to 8.5" x 14" / 52–120 gsm
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60–216 gsm
Paper input capacity	Standard: 350 sheets Max.: 900 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 11" / 60–90 gsm
Tray 2 (optional)	250 or 550 sheets / 8.5" x 11" to 8.5" x 14" / 60–90 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" custom paper sizes / 60–216 gsm
Automatic duplexing	8.5" x 11" to 8.5" x 14" / 60–90 gsm
Output capacity	Max.: 150 sheets
Copy/print volume	Max.: 50,000 pages/month ¹
Toner lifetime	15,000 pages ²
Imaging unit lifetime	60,000 pages
Power consumption	110 V / 60 Hz, less than 550 W (system)
System dimensions	15.7" x 16.9" x 18.4" (H x W x D)
System weight	Approx. 43 lb

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Print speed	Up to 38 ppm (letter)
Autoduplex speed	Up to 19 ppm (letter)
1st copy out time	6.5 sec.
Warm-up time	Approx. 90 sec. ³
Copy resolution	600 x 600 dpi
Multi-copy	1–999
Original format	4" x 6" to 8.5" x 14"
Magnification	25–400% in 1% steps; auto zooming
Copy functions	Duplex copy (1-sided to 2-sided only), 2-in-1, 4-in-1, poster, density adjustments

PRINTER SPECIFICATIONS

Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
PDL	PCL5e, PostScript
Operating systems	Windows (x32/x64): 7 / 8 / 8.1 / 10 Windows Server (x32/x64): 2008 / 2008 R2 / 2012 ⁴ / 2012 R2 / 2016 Macintosh OS X 10.9 or later Linux
Printer fonts	89 PCL Latin, 158 PostScript
Print functions	Confidential print, combination, n-up, overlay, watermark

SCANNER SPECIFICATIONS

Scan speed	Up to 45 opm (mono)
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-FTP, Network TWAIN
File formats	TIFF, PDF, JPEG, XPS
Scan destinations	500 (shared with fax), LDAP support

FAX SPECIFICATIONS

Fax	Super G3
Transmission	Analog, PC-fax
Resolution	Max.: 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	500 (shared with scan), LDAP support
Functions	Polling, time shift, PC-fax

OPTIONS

PF-15 Paper tray	8.5" x 11" to 8.5" x 14" / 250 sheets / up to 120 gsm
PF-16 Paper tray	8.5" x 11" to 8.5" x 14" / 550 sheets / up to 120 gsm
DK-P02 Copier desk	Ensures ergonomic height and provides storage space for print media, etc.
CS-1 Convenience stapler	Convenient stapling of up to 50 prints per set

SYSTEM FEATURES

Security	IP filtering and port blocking, IPsec support, IEEE 802.1x support, user authentication, secure print
Software	Net Care Device Manager WebConnection Data Administrator Direct Print Konica Minolta Mobile

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

² The bizhub 3622 ships with a starter toner cartridge (2,500 yield).

³ Warm-up time may vary depending on the operating environment and usage.

⁴ Supports x64 only.



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: 3622SS
7/2018-C