

intelliFAX-4750e

BUSINESS CLASS FAX,
PHONE & COPIER

LASER

FEATURING

- Super G3, 33.6K bps High Speed Fax Modem
- Up to 15ppm Laser Engine for printing of faxes and copies
- 8MB Memory stores up to 600 Pages* for Out-of-Paper Reception and Memory Transmission
- Up to 50-Page Auto Document Feeder
- 250 Sheet Paper Capacity



8MB
MEMORY with
BROADCASTING

DUAL
Scan a fax into memory while
another is being sent or received.
ACCESS

250 SHEET
PAPER CAPACITY

At your side.™

brother®

intelliFAX-4750e

BUSINESS CLASS FAX, PHONE & COPIER

LASER



Featuring...

- Super G3, 33.6K bps High Speed Fax Modem
- Up to 15ppm Laser Engine for printing of faxes and copies
- 8MB Memory stores up to 600 Pages* for Out-of-Paper Reception and Memory Transmission
- Up to 50-Page Auto Document Feeder
- 250 Sheet Standard Paper Capacity (adjustable for letter or legal paper)
- Optional Second Lower Paper Tray Unit for additional 250 sheets**
- Quickly scan faxes as fast as 2 secs./page*
- 232 Station Auto Dialing (32 One-Touch Keys, plus up to 200 speed dial locations)
- High Yield Toner Cartridges deliver low printing costs per page†
- Fax Broadcasting to up to 282 locations
- Multi-Copying up to 99 copies, plus Sorting
- Copy Reduction and Enlargement, 50%-200%

8MB
MEMORY with
BROADCASTING

DUAL
Scan a fax into memory while
another is being sent or received.
ACCESS

SUPER G3
33.6K bps High-Speed
FAX

Other Standard Features

- Dual Access capability lets you scan faxes into memory while the unit is busy sending or receiving
- 4-Day Battery Back-up for Fax Memory
- Fax Security with password controlled access
- Auto Fax/Tel Switching for receiving fax and voice calls on a single phone line
- Fax Forwarding, Paging and Remote Fax Retrieval
- Telephone Handset
- Caller ID and Distinctive Ring Detection ready‡
- Built-in Parallel and USB interfaces for future printing needs*

UP TO
6,000 PAGE[†]
YIELD
TONER

250 SHEET
PAPER CAPACITY

* Based on Brother #1 Chart with JBIG coding and standard resolution.

** Requires additional purchase.

† Based on 5% page coverage using optional TN460 Toner Cartridge (cartridge requires additional purchase).

‡ Check with local phone company for availability of and charges for these services.

• Printer drivers downloadable at no charge from <http://www.brother.com>

All trademarks and registered trademarks referenced herein are the property of their respective companies.

© 2002 BROTHER INTERNATIONAL CORPORATION, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911
For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA ONLY)
or visit our web site at www.brother.com.

All specifications are subject to change without notice. Printed in USA. CATFX4750e

PRODUCT SPECIFICATIONS

Approved:	UL and FCC
Unit Dimensions:	17.4" x 17.1" x 12.7"
Unit Weight:	10.6 lbs.
Carton Dimensions:	22.0" x 20.3" x 18.1"
Carton Weight:	36.3 lbs.
UPC Code:	0 12502 60283 5
Compatibility:	ITU-T Group 3
Coding Method:	MH/MR/MMR/JBIG
Modulation:	33600/31200/28800/26400/2400/ 21600/19200/16800/14400/12000/ 9600/7200/4800/2400 bps
Transmission Time:	As fast as 2 seconds per page (Brother #1 Chart, JBIG)
Printing Method:	Electrophotography
Copy Speed:	Up to 15 copies per minute
Document Input Width:	5.8" to 8.5"
Recording Paper Size:	8.5" x 11" / 8.5" x 14"
Scanning/Recording Width:	8.2"
Resolution Standard:	203 x 98 lines/inch
Fine Mode:	203 x 196 lines/inch
Superfine:	203 x 392 lines/inch
Display:	LCD, 2 lines by 16 characters
Gray Scale:	64 shades
Interfaces (Standard)	USB and High-Speed, Bi-Directional, Parallel Centronics (cables not included)
Dialing System:	Selectable Pulse/Tone
Speaker Type:	Monitor
Communication Source:	Public Switched Telephone Network
Connection Requirements:	USOC RJ11C Modular Jack (or equivalent)
Power Supply:	120V, 50/60 Hz
Power Consumption:	Sleep Mode: 10W or less Standby: 70W or less Average Operating (Copying): 350W
Noise Level:	53 dBA Printing 30 dBA Standby
Operating Environment:	50° to 90.5° F
Standard Toner Cartridge:	Up to 3,000 pages @ 5% coverage

OPTIONAL ACCESSORIES‡

TN430:	Standard Yield Toner Cartridge (Up to 3,000 pages @ 5% coverage)
TN460:	High Yield Toner Cartridge (Up to 6,000 pages @ 5% coverage)
DR400:	Replacement Drum Unit
LT400:	Second Lower Paper Tray Unit (Additional 250 Sheets)
NC-8100h:	10/100 BaseTX Ethernet Network Print/Fax Server

‡ Requires additional purchase.

Use only
GENUINE
brother
supplies

At your side.™
brother®

www.brother.com