

# PRODUCT SPECIFICATIONS



## Main Unit

### Type

Color Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
 Optional: Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

### Memory

3.0 GB RAM

### Hard Disk Drive

Standard: 250 GB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,  
 Wireless LAN (IEEE 802.11 b/g/n)

### Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),  
 USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets

Maximum: 2,300 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet  
 Stack Bypass

Optional: Dual 550-sheet Paper Cassettes  
 (CASSETTE FEEDING UNIT-API),

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum: 3,450 Sheets  
 (with External Finisher and Copy Tray)

### Finishing Capabilities

Standard: Collate, Group

With Inner Shift

Sorter: Collate, Group, Offset

With Inner  
 Finisher: Collate, Group, Offset, Staple, Staple-Free  
 Staple, Staple On Demand

With External  
 Finishers: Collate, Group, Offset, Staple, Booklet, Staple-  
 Free Staple, Staple On Demand, Hole Punch  
 (Optional)

### Supported Media Types

Paper

Cassettes (1/2): Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Bond, Transparency, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Labels, Bond, Coated,  
 Transparency, Tracing, Envelope

Cassette

Feeding Unit-API: Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Bond, Transparency

### Supported Media Sizes

Paper  
 Cassette 1: Letter, Executive, Statement-R, Envelope  
 [No.10 (COM10), DL, ISO-C5], Custom Size  
 (5-1/2" x 7-1/8" to 11-3/4" x 8-1/2")

Paper Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
 Executive, Statement-R, Envelope  
 [No.10 (COM10), Monarch, DL], Custom Size  
 (5-1/2" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
 Executive, Statement, Statement-R,  
 Envelope [No.10 (COM10), Monarch,  
 DL, ISO-C5], Envelope Custom Size  
 (3-7/8" x 3-7/8" to 12-5/8" x 18"),  
 Custom Size (3-7/8" x 5-1/2" to  
 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to  
 12-5/8" x 18")

Cassette Feeding Unit-API:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (5-1/2" x 7-1/8" to 12" x 18")
----------------------------	---

#### Supported Media Weights

Cassettes:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m <sup>2</sup> )
Stack Bypass:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m <sup>2</sup> )

#### Print/Copy Speed (BW and Color)

C3530i II:	Up to 30 ppm (Letter)
	Up to 20 ppm (Letter-R)
	Up to 15 ppm (Legal)
	Up to 15 ppm (11" x 17")
C3525i II:	Up to 25 ppm (Letter)
	Up to 20 ppm (Letter-R)
	Up to 15 ppm (Legal)
	Up to 15 ppm (11" x 17")

#### Warm-up Time

From Power On:	34 Seconds
From Sleep Mode:	10 Seconds
Quick Startup Mode:	10 Seconds <sup>1</sup>

#### Dimensions (W x D x H)

22-1/4" x 29-1/4" x 45-1/5" (565 mm x 742 mm x 1148 mm)<sup>2</sup>

#### Installation Space (W x D)

Basic:	Stack Bypass + Cassette Drawers open: 38-1/2" x 44-1/4" (978 mm x 1123 mm) <sup>2</sup>
Fully Configured:	63-3/4" x 44-1/4" (1620 mm x 1123 mm) <sup>3</sup>

#### Weight

Approx. 213.9 lb. (97 kg)<sup>4</sup>

## Print Specifications

#### Print Resolution (dpi)

1200 x 1200

#### Standard Page Description Languages

UFR II, PCL®6, Adobe® PS® 3

#### Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access<sup>5</sup>

#### Supported File Types

PDF, TIFF, JPEG, EPS, XPS

#### Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

#### Fonts

PCL fonts:	93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese), <sup>6</sup> Barcode Fonts <sup>7</sup>
PS fonts:	136 Roman

#### Operating System<sup>8</sup>

UFR II/PS:	Windows Vista®/Server 2008/Windows® 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.7 or later)
PCL:	Windows Vista/Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016

#### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction

## Copy Specifications

#### First-Copy-Out Time (Letter)

As fast as 5.9 seconds (BW)/8.2 seconds (Color)

#### Multiple Copies

Up to 999 Copies

#### Copy Exposure

Automatic or Manual (9 Levels)

#### Magnification

25%-400% (1% Increments)

#### Preset Reductions

25%, 50%, 64%, 73%, 78%

#### Preset Enlargements

121%, 129%, 200%, 400%

#### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

#### Special Copy Features

Book to Two Pages, Two-Sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different-Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Job Done Notice, Mirror Image, Copy ID Card, Multi Sheet Feed Detection, Free Size Original, Adjust One-Touch Color, Color Balance, Area Designation

## Scan Specifications

#### Type

Single-pass Duplexing Automatic Document Feeder

#### Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

#### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

#### Document Feeder Supported Media Weights

BW Original:	13 lb. Bond to 58 lb. Cover (50 to 157 g/m <sup>2</sup> )
CL Original:	17 lb. Bond to 58 lb. Cover (64 to 157 g/m <sup>2</sup> )

#### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

#### Pull Scan

Color Network ScanGear2 for both Twain and WIA  
Supported OS: Windows Vista/7/8.1/10/  
Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016

#### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

#### Scan Speed (Letter)

Single-sided Scanning (BW and Color):  
80 ipm (300 dpi)/51 ipm (600 dpi)  
Double-sided Scanning (BW and Color):  
160 ipm (300 dpi)/51 ipm (600 dpi)

## Send Specifications

#### Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

#### Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

#### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

#### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### Communication Protocol

File:	FTP, SMB, WebDAV
Email/I-Fax:	SMTP, POP3, I-Fax (Simple, Full)

#### File Format

Standard:	TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Office Open XML (PowerPoint®, Word), Digital Signature (PDF/XPS))
Optional:	PDF (Trace & Smooth)

#### Universal Send Features

Original Type Selection, Two-Sided Original, Book to Two Pages, Different-Size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

## Fax Specifications

#### Maximum Number of Connection Lines

2

#### Modem Speed

Super G3:	33.6 Kbps
G3:	14.4 Kbps

#### Compression Method

MH, MR, MMR, JBIG

#### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

#### Sending/Recording Size

Statement-R to 11" x 17"

#### Fax Memory

Up to 30,000 Pages

#### Speed Dials

Max. 200

#### Group Dials/Destinations

Max. 199 Dials

#### Sequential Broadcast

Max. 256 Addresses

#### Memory Backup

Yes

#### Fax Features

Original Type Selection, Two-Sided Original, Book to Two Pages, Different-Size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

#### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

#### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported Windows (Windows Vista/7/8/8.1/10)  
Client PC:  
Concurrent Connections (Max.):  
SMB: 64  
WebDAV: 3 (Active Sessions)

#### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

**Advanced Box Features:**

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

**Memory Media**

Standard: USB

**Security Specifications**

**Authentication**

Standard: Universal Login Manager, uniFLOW Online Express,<sup>9,10</sup> User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in

Optional: uniFLOW

**Data**

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)

Optional: Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

**Network**

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

**Document**

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration

Optional: User Signatures, Document Scan Locking

**Environmental Specifications**

**Operating Environment**

Temperature: 50 to 86 °F  
Humidity: 20 to 80 % RH (no condensation)

**Power Requirements**

120-127V AC 60 Hz, 7.5 A

**Plug (Main Unit)**

NEMA 5-15P

**Power Consumption**

Maximum: Approx. 1.5 kW  
Standby: Approx. 44.1 W  
Sleep Mode: Approx. 0.8 W<sup>11</sup>  
Typical Electricity Consumption (TEC) Rating:  
C3530i II: 1.2 kW  
C3525i II: 1.0 kW

**Standards**

ENERGY STAR® Certified  
Rated EPEAT® Gold<sup>12</sup>

**Consumables**

**Toner**

GPR-53 Toner<sup>13</sup>

**Toner Yield (Estimated @ 5% Coverage)**

Black: 36,000 Images  
Color (C,M,Y):<sup>13</sup> 19,000 Images

**Paper Supply Options**

**CASSETTE FEEDING UNIT-API**

Paper: 550 Sheets x 2 Cassettes  
Capacity: [20 lb. Bond (80 g/m<sup>2</sup>)]  
Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, and Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7 x 182.0 to 304.8 x 457.2 mm)]

Paper Weight: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

Power Source: From the Main Unit  
Dimensions (W x D x H): 22-1/4" x 24-1/4" x 9-3/4" (565 mm x 615 mm x 248 mm)  
Weight: Approx. 35.3 lb. (16 kg)

**Output Options**

**INNER 2-WAY TRAY-J1**

Number of Trays: 2  
Total Output Capacity: Upper Tray: 100 Sheets  
Lower Tray: 250 Sheets  
Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)

Paper Size: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")  
Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Dimensions (W x D x H): 16-7/8" x 16" x 3" (427 mm x 407 mm x 76 mm)  
Weight: Approx. 1.3 lb (0.6 kg)

**INNER SHIFT SORTER-A1**

Number of Trays: 1  
Tray Capacity: Letter/Executive (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R/Statement/Statement-R (125 Sheets)

Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m<sup>2</sup>)

Paper Size Non-Sort: 12"x18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size: 3-7/8" x 3-7/8" to 12-5/8" x 18", Custom Size: 3-7/8" x 5-1/2" to 12-5/8" x 18"

Shift: 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R

Dimensions (W x D x H): 21-1/4" x 20-5/8" x 4-1/2" (538 mm x 523 mm x 114 mm)  
Weight: Approx. 6.6 lb (3.0 kg)

**INNER FINISHER-K1**

Number of Trays: 2  
Top Tray Capacity: Letter/Statement/Statement-R/Executive (100 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (50 Sheets)  
Lower Tray Capacity: Letter/Statement/Statement-R/Executive (500 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (250 Sheets)

Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m<sup>2</sup>)

Staple Position: Corner, Double  
Staple Capacity Corner Staple and Double Staple  
Letter/Executive: 50 Sheets (14 to 24 lb. Bond)  
11" x 17"/Legal/Letter-R: 30 Sheets (14 to 24 lb. Bond)

Staple-Free Staple  
11"x17"/Letter: 5 Sheets (14 to 17 lb. Bond)  
4 Sheets (17.3 to 21.7 lb. Bond)  
3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions (W x D x H): 23-3/4" x 20-5/8" x 7-3/8" (604 mm x 525 mm x 188 mm)  
Weight: Approx. 17.6 lb (8 kg)

**STAPLE FINISHER-AA1 (External)**

Number of Trays: 2  
Top Tray Capacity: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray Capacity: Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)

Staple Position: Corner, Double

Staple Capacity Corner Staple and Double Staple  
Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Staple-Free Staple:  
11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m<sup>2</sup>)]  
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m<sup>2</sup>)]  
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m<sup>2</sup>)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions 25-1/8" x 24-1/2" x 40" (637 mm x 623 mm x 1016 mm)  
Weight: Approx. 66.1 lb (30 kg)

**BOOKLET FINISHER-AA1 (External)**

Number of Trays: 2  
Top Tray Capacity: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)  
Lower Tray Capacity: Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)

Staple Position: Corner, Double

Staple Capacity Corner Staple and Double Staple  
Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Staple-Free Staple  
11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m<sup>2</sup>)]  
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m<sup>2</sup>)]  
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m<sup>2</sup>)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Booklet-Stitch Paper Size: 12" x 18", 11" x 17", Legal, Letter-R, Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]  
Booklet-Stitch Staple Capacity: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m<sup>2</sup>)] [including one cover sheet up to 140 lb. Index (256 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions 25-1/8" x 24-1/2" x 40" (637 mm x 623 mm x 1016 mm)  
Weight: Approx. 116.8 lb (53 kg)

**2/3-HOLE PUNCHER UNIT-A1**

(Requires either the STAPLE FINISHER-AA1 or BOOKLET FINISHER-AA1)

Acceptable Punch Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Acceptable Punch Paper Size Two holes: 11" x 17", Legal, Letter, Letter-R, Executive  
Three holes: 11" x 17", Letter, Executive  
Power Source: From the Main Unit

## Hardware Options

### Card Readers

IC CARD READER BOX-C1  
MiCARD PLUS PROXIMITY CARD READER  
COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-B5

### Others

CABINET TYPE-R  
COPY TRAY-J2  
UTILITY TRAY-B1  
PLATEN COVER TYPE W  
USB KEYBOARD

## Security Options

### Document Security

DOCUMENT SCAN LOCK KIT-B1  
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON  
CRITERIA CERTIFICATION<sup>14</sup>

### Data Security

REMOVABLE HDD KIT-AK2

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1

### Barcode Printing

BARCODE PRINTING KIT-D1

### System Accessories

SERIAL INTERFACE KIT-K3  
COPY CONTROL INTERFACE KIT-A1  
CONNECTION KIT-A1 FOR BLUETOOTH LE  
NFC KIT-C1  
MEAP WEB CONNECTION KIT-G3<sup>15</sup>

### Fax Accessories

SUPER G3 FAX BOARD-AU1  
SUPER G3 2ND LINE FAX BOARD-AU1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1  
BRAILLE LABEL KIT-F1

### Staples

STAPLE-P1<sup>16</sup>  
STAPLE CARTRIDGE-Y1<sup>17</sup>

<sup>1</sup> Time from device power-on to when copy jobs can be programmed.

<sup>2</sup> Includes main unit and either Cassette Feeding Unit-API or Cabinet Type-R.

<sup>3</sup> Includes main unit and either Cassette Feeding Unit-API or Cabinet Type-R and Staple/Booklet Finisher-AA1.

<sup>4</sup> Includes main unit, ADF, consumables, and Cassette Feeding Unit-API.

<sup>5</sup> PDF print from Web sites is supported.

<sup>6</sup> Requires the optional PCL International Font Set-A1.

<sup>7</sup> Requires the optional Barcode Printer Kit-D1.

<sup>8</sup> Other operating systems and environments, including AS/400, UNIX, Linux and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>9</sup> No charge for this solution; however activation is required.

<sup>10</sup> Check for availability.

<sup>11</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.

<sup>12</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>13</sup> GPR-53L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 8,500 images.

<sup>14</sup> Will launch at a later date.

<sup>15</sup> No charge for this option; however it does need to be ordered.

<sup>16</sup> Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.

<sup>17</sup> Used for booklet finishing only. 2 cartridges per case. 2,000 staples per cartridge.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. It indicates that this model has been upgraded to new system software and includes additional security features as standard. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2018 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



0318R1-RA35IIS- PDF-IH

